

Mini Rack

Prysmian Part Number: XEXSC00663



The Mini Rack (MR) is a reduced width rack for use in the exchange or central office where space is at a premium. The MR can be fitted with Compact Sub-Racks (CSR), which can each accommodate up to 24 connectors on a splice and patch basis. The Compact Sub Racks have 12 splice trays offering single circuit management. Up to five Compact Sub-Racks can be installed into the Mini Rack providing a maximum capacity of 120 fibres on a splice + patch basis.

Features and Benefits

- Easy installation and maintenance due to removable panels.
- Allows the termination of up to 5 cables with entry from the top or the bottom.
- Up to 5 Compact Sub-Racks can be fitted.
- Allows single circuit management.
- Compact Sub-Racks are available with a wide range of connectors such as SC, FC, ST, LC and E2000.
- Compact Sub-Racks can also be used to store patch cord over-lengths.
- Easy fibre management, pivoting main tray allows all splicing modules to be accessed easily.
- Tube guides allow access of transport tube with fibres coming from the main rack or another sub-rack.
- The rack is supplied with a Cable Head Splitting Device which contains 5 tubes at 3 metres long. The device is used to breakout a cable in the rack and route the fibres to any of the Compact Sub-Racks within the rack.

Kit Contents

- Main Frame
- Plate for fixing cable splitting devices.
- 1 cable splitting device with 5 x 3m tubes

Additional Items

- Compact Sub-Rack
- Additional Cable Head Splitting Device

Technical Data

- Max Fibre capacity: 120 on a single circuit and splice + patch basis
- Required space envelope (mm): (w) 300 x (d) 300 x (h) 2200
- Operating temperature: -20°C to + 50°C (5 to 95% RH)
- Materials:-
 - Internal Metalwork: Mild Steel
 - External Metalwork: Mild Steel
 - Plastics: PC ABS (Fire Retardant)
- Finish:-
 - Internal Metalwork: Zinc passivate (Clear)
 - External Metalwork: Painted Light Grey (RAL 7035)
 - Plastic: Light Grey (RAL 7035)

Logistics

- Packing Dimensions (mm): (w) 2320 x (d) 635 x (h) 310
- Packed Weight (kg): 113
- Net weight (kg): 105

Additional Items

Compact Sub-Rack

The Compact Sub-Rack is a 24 fibre sub-rack, which is pre-assembled and cabled in the factory. It is designed to be installed in the mini rack. During the installation splicing is carried out without removing the cables. The sub-rack is supplied with 12 single circuit splice trays and 24 adapters and pigtails. A variety of different connector types can be accommodated.

Prysmian Part Nos.

- XEXSC00668*** - CSR with 24 x FC/UPC pigtails and adapters
- XEXSC00669*** - CSR with 24 x FC/APC pigtails and adapters
- XEXSC00670*** - CSR with 24 x SC/UPC pigtails and adapters
- XEXSC00671*** - CSR with 24 x SC/APC pigtails and adapters
- XEXSC00672*** - CSR with 24 x ST pigtails and adapters
- XEXSC00673*** - CSR with 24 x E2000/UPC pigtails and adapters
- XEXSC00674*** - CSR with 24 x E2000/APC pigtails and adapters
- XEXSC00675*** - CSR with 24 x LC/UPC pigtails and adapters
- XEXSC00676*** - CSR with 24 x LC/APC pigtails and adapters

XEXSC00665 – Additional Cable Head Splitting Device



Please contact your local sales office listed on www.prysmiangroup.com

© Prysmian Group 2012, All Rights Reserved.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed correct at the time of issue. Prysmian Group reserves the right to amend this specification without notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.